

Product information



Part number: A.007808

HMI Ex Zone 2 PC

Capacitive Touch Screen

Features

- ✓ Sunlight viewable, glove-friendly touchscreen
- ✓ Ethernet, fiber optics or WiFi communications
- ✓ -40°C to +60°C operating temperature
- ✓ Lightweight
- ✓ VESA, yoke and panel mounted
- ✓ IP66, ATEX Ex-n Zone 2
- ✓ Designed for field maintainability

Specifications

Article number	A.007808
Type of Protection	ATEX/IECEX Ex nA [ic] IIC T4 Gc (Gc) Ex tc IIIC T135°C Dc CSA Class I Div 2, AEx Class I Zone 2
Display Size	15"
Display Type	Sunlight viewable Glove-friendly capacitive LCD Touchscreen
Display Resolution	15inch: XGA 1024 x 768
Processor Options	Intel® Core™ 2 Duo 2.16Ghz
Operating System	Windows 7 Professional 32bit
HDD/SDD Options	Rugged 64GB SSD
Compact Flash	None
RAM	2GB
Serial Communication	RS232
Keyboard/mouse	External Exi PS/2 interface
Ingress protection	IP66 / NEMA4 and NEMA 4X
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Storage Temperature	-40°C to +85°C (-40°F to +185°F)
Power input	90-260V AC
Weight	12.6 kg / 27.8 lbs
Dimensions	450mm x 395mm x 202mm
Mounting options	VESA, Yoke, Panel
Shocks	In accordance with BSEN60068-2-27:2009
Vibrations	In accordance with BSEN60068-2-6:2008