

Product information



Part number: A.008408

HMI Ex Zone 2 PC Capacitive Touch Screen

Features

- Sunlight viewable, glove-friendly touchscreen
- Ethernet, fiber optics or WiFi communications
- -40°C to +60°C operating temperature
- Lightweight
- VESA, yoke and panel mounted
- IP66, ATEX Ex-n Zone 2
- Designed for field maintainability

0	
Specifications	
Article number	A.008408
Type of Protection	ATEX/IECEx Ex nA [ic] IIC T4 Gc (Gc), Ex tc IIIC T135°C Dc
	CSA Class I Div 2, AEx Class I Zone 2, Zone 21
Display Size	19"
Display Type	Sunlight viewable, Glove-friendly, capacitive LCD Touchscreen
Resolution	SXGA 1280 x 1024
Processor	Core i7-3517UE, 1.7GHz (TPM Compliant)
Operating System	Windows 7 Professional 32bit
HDD/SDD Options	Rugged 64GB SSD
Compact Flash	None
RAM	2GB
Serial Communication	RS232 and RS422/RS485
Keyboard/mouse	External Exi PS/2 interface
Ingress protection	IP66 / NEMA4 and NEMA 4X
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Storage Temperature	-40°C to +85°C (-40°F to +185°F)
Power input	90-260V AC
Weight	12.2 kg / 26.9lbs
Dimensions	476mm x 427mm x 90mm
Mounting options	VESA, Yoke, Panel
Shocks	In accordance with BSEN60068-2-27:2009
Vibrations	In accordance with BSEN60068-2-6:2008