

## Product information



Part number: A.008910

### Ex Z1 HMI panel PC 22"

- ModularPanelPC/ThinClientOperatorStation,22" display
- Zone 1, 21, Class I, Zone 1 / Div 2, stainless steel enclosure IP66, GMP compliant
- Robust touch screen, protected behind reflection-free glass
- Data transmission via Ethernet copper up to 100 m and / or glass fibre up to 10 km



The A.008910 Operator Stations are modular explosion-proof Panel PCs or Thin Clients for zones 1 and 21. Their brilliant 22 inch widescreen displays with robust multitouch capable touch screen have a resolution of 1920 x 1080 pixels (format 16:9). The enclosures in SS304 or SS316L stainless steel are available with front opening in cleanroom-compatible design, also in different mounting variants. You can configure country-specific keyboards, pointing instruments, RFID read-ers and barcode readers, processors, memory variants, interfaces as well as SSDs. Data transmission is via Ethernet as 10/ 100/ 1000Base- TX, 1000Base- SX or 1000Base- LX.

## Technical Data

### General

Product description	22" Panel PC
Technology	Panel PC
HMI type	Rugged Panel

### Explosion Protection

Application range (zones)	1 2 21 22
Application range (divisions)	Class I, Zone 1 Class I, Division 2 Class II, Division 1 and 2 Class III
IECEX certification	IECEX UL 23.0007X
ATEX certification	UL 23 ATEX 2902X
IECEX gas explosion protection	Ex eb ib qb [ib] [ja Ga] IIC T4 Gb
IECEX dust explosion protection	Ex tb [ib] [ja Da] IIIC T115°C Db
ATEX gas explosion protection	Ⓔ II 2(1) G Ex eb ib qb [ib] [ja Ga] IIC T4 Gb
ATEX dust explosion protection	Ⓔ II 2(1) D Ex tb [ib] [ja Da] IIIC T115°C Db

## Product information

## Electrical Data

Power supply	24 VDC or 230 VAC
Rated operational voltage DC	DC option: 24 V
Rated voltage range DC	19.2 V - 31.2 V
Rated operational voltage AC	AC option: 110 / 230 V
Rated voltage range AC	85 V - 250 V
Processor type	E-Box Standard: Intel® ATOM™ E3940 E-Box Pro: Intel® ATOM™ E3940 or Intel® Core i5™ 8365UE
Processor details	Intel® ATOM™: 1.6 / 1.8 GHz, Quad Core Intel® Core i5™: 1.6 / 4.1 GHz, Quad Core, 8 threads, 6 MB Cache
RAM	ATOM: 4 GB i5: 16 GB
Data memory	ATOM: 64 GB / 128 GB i5: 240 GB
Graphics controller	ATOM: Intel® HD graphics 500 i5: Intel® UHD graphics 620
Operating system	None None / PXE Boot Windows™ 10 2019 LTSC IGEL OS
Operating system note	IGEL OS: pre-installed without licence
	None Windows™ 10 2019 LTSC 32-Bit Windows™ 10 2019 LTSC 64-Bit Windows™ 10 2019 LTSC 64-Bit Remote HMI Firmware V6 Windows™ 10 2019 LTSC 64-Bit Movicon 11 IGEL OS
Ethernet / Data	2x 10/100/1000Base-TX oder 1x 10/100/1000Base-TX + 2x 1000Base-SX oder 1x 10/100/1000Base-TX + 2x 1000Base-LX
Data cable	TX: min. CAT5 SX: FO cable 50/125 µm or 62,5/125 µm LX: FO cable 9/125 µm
Data cable length	TX: 100 m SX: 50 µm: 500 m SX: 62.5 µm: 300 m LX: 10 km
Data cable notice	TX: Ex e screw terminals
Interface medium	TX: min. CAT5 Data transmission SX: multi-mode optical cable LX: single mode optical cable
Interface USB	2x USB Ex ia (for keyboard, pointing device), 1x USB Ex ib (for USBi-Drive) 1x USB Ex e (LS/FS/HS 500 mA) 1x USB Ex e (LS/FS/HS for Bus Powered Devices only, 500 mA)
Interface serial	RS-232 / RS-422 / RS-485 switchable
Plug version FO	SX / LX: LC - Duplex socket
Battery	> 5 years
Capacitor buffered	approx. 4 days

## Product information

### Electrical Data

Interface USB	2x USB Ex ia (for keyboard, pointing device), 1x USB Ex ib (for USBi-Drive) 1x USB Ex e (LS/FS/HS 500 mA) 1x USB Ex e (LS/FS/HS for Bus Powered Devices only, 500 mA)
Interface serial	RS-232 / RS-422 / RS-485 switchable
Plug version FO	SX / LX: LC - Duplex socket
Battery	> 5 years
Capacitor buffered	approx. 4 days

### Display

Display version	TFT colour display
Display version 2	16.7 million colours
Display size inch	22
Display size centimetres	55
Display resolution	1920 x 1080; 1680 x 1080; 1280 x 1024
Total pixels	1920 x 1080
Display dimensions	16:9
Display brightness	350 cd/m <sup>2</sup>
Display contrast	1:1000
Touchscreen	Yes
Touchscreen technology	Projected capacitive (PCAP), multi-touch
Touchscreen activation	Touch, no activation pressure required
Touchscreen input method	Finger, thin gloved finger or special gloves, conductive stylus
Touchscreen durability	Very good
Touchscreen transmissivity / optic	Very good
Touchscreen surface contaminants	Unaffected (may however be affected by conductive fluids such as saltwater)
Touchscreen abrasive resistance	No abrasion by finger or rubber
Backlight	LED Technology
Backlight service life	50000 h +25 °C
Front plate (display)	Glass, polyester on powder-coated aluminium
Function keys	Optionally via keyboard with integrated trackball, joystick or touchpad
Softkeys	Optionally via keyboard with integrated trackball, joystick or touchpad
Cursor keys	Optionally via keyboard with integrated trackball, joystick or touchpad
Alphanumeric keys	Optionally via keyboard with integrated trackball, joystick or touchpad
System keys	Input deactivation, display brightness, function key

### Ambient Conditions

Ambient temperature operation	-20 °C ... +50 °C
Storage temperature	-40 °C ... +60 °C
Relative humidity	10 to 90 % at +40 °C, non-condensing
Positive pressure operation	< = 20 mbar

### Mechanical Data

Dimensions (WxHxD)	without keyboard: 708 mm x 524 mm x 176 mm
--------------------	--

## Product information

### Mechanical Data

Material front	Stainless steel, glass and polyester on powder-coated aluminium
Material back	Stainless steel
Ingress protection	IP66
IP enclosure front	IP66
IP enclosure back	IP66

### Mounting / Installation

Enclosure material	Stainless steel enclosure V2A or V4A
Enclosure design	Cleanroom compatible
Mounting option	Wall mounting or mounting on stand / elbow

### Components

Keyboard	optional, 105 keys with trackball / joystick / touchpad
----------	---